

Drive with 313D2 pumphead



300 series cased pump

Features and benefits

- Manual or remote 4-20 mA or 0-10 V analogue auto-control or RS232 control commands
- Up to 133:1 enhanced digital manual speed control
- Keypad lock prevents tampering or accidental changes
- MemoDose facility for accurate single-shot dosing
- Digital TTL inputs for run/stop and direction
- Instantly reversible
- Two-year warranty



Technical specifications

	Drive with 313D2 pumphead
Pumphead number of rollers	3
Pumphead number of channels	1
Max. flow rate	2000 ml/min
Min. flow rate	0.81 ml/min
Speed control ratio	133:1, 27:1
Max. operating speed	400 rpm
Min. operating speed	3 rpm
Operating temperature range	5 to 40 °C
Operating temperature range	40 to 104 °F
Weight	4.7 kg
Weight	10.4 lbs
Drive control options	Du, E, S, U
Drive standards	CE, cETLus
Drive ingress rating	IP31
Drive humidity	80% up to 31°C, 88°F, decreasing linearly to 50% at 40°C, 104°F
Drive noise	<70dB(A) at 1m
Max. altitude	2000
Drive power supply	1ph, 100-120 V, 220-240 V 50/60 Hz, 100 VA
Compatible tubing bore size	1.6, 3.2, 4.8, 6.4 mm
Compatible tubing wall thickness	2.4 mm

Materials of construction

	Drive with 313D2 pumphead
Bearings	Carbon steel, Sintered bronze
Drive casework	ABS (Acrylonitrile butadiene styrene), Powder coated aluminum LM24
Pumphead body assembly	Glass filled polypropylene, IXEF (Polyarylamide), Stainless steel
Pumphead roller assembly	MoS2 filled Nylon 6 (Nylatron)
Pumphead rotor assembly	Electroless nickel plated hardened steel, Glass filled Nylon
Pumphead track	IXEF (Polyarylamide)
Tube clamp assembly	Glass filled Nylon

Information listed covers the complete range.

For detailed specifications of individual models/components refer to user manual or contact WMFTS representative.

Control options

Functionality	323E	323S	323U	323Du
Manual control				
Keypad speed control	✓	✓	✓	✓
15-400rpm 27:1 speed control	✓			
3-400rpm 133:1 speed control		✓	✓	✓
1.5-220rpm 147:1 speed control		✓	✓	✓
MemoDose for accurate single shot dosing		✓	✓	✓
Remote control				
Run/Stop, direction change via contact closure or 5V TTL			✓	✓
Remote operation of MemoDose (hand/foot switch)			✓	✓
Analogue speed control				
Inputs; 0-10V or 4-20mA			✓	✓
RS232 digital communication				
Digital serial control				✓
Security				
Keypad lock to protect set-up		✓	✓	✓

Product codes

Drives and pumpheads product codes		
Description		Partcode
323E	Drive only	036.3124.000*
323S	Drive only	036.3134.000*
323U	Drive only	036.3144.000*
323Du	Drive only	036.3154.000*
313DW2	Three-roller pumphead for 2.4 mm wall tube	033.3551.000

*Replace last 0 with A, E or U for American, European or UK mains supply (American 110 V 1 ph 60 Hz)

If required for use with STA-PURE and Chem-Sure tubing, please contact Watson-Marlow Bredel technical support for drive and pumphead selection

Tubing product codes				
Bore/wall (mm)	Bioprene	Marprene	Platinum Silicone	
1.6 / 2.4	903.0016.024	902.0016.024	913.A016.024	
3.2 / 2.4	903.0032.024	902.0032.024	913.A032.024	
4.8 / 2.4	903.0048.024	902.0048.024	913.A048.024	
6.4 / 2.4	903.0064.024	902.0064.024	913.A064.024	
8.0 / 2.4	903.0080.024	902.0080.024	913.A080.024	
Bore/wall (mm)	STA-PURE®	STA-PURE®Series PCS	STA-PURE®Series PFL	Chem-Sure®
1.6 / 2.4	960.0016.024	961.0016.024	966.0016.024	965.0016.024
3.2 / 2.4	960.0032.024	961.0032.024	966.0032.024	965.0032.024
4.8 / 2.4	960.0048.024	961.0048.024	966.0048.024	965.0048.024
6.4 / 2.4	960.0064.024	961.0064.024	966.0064.024	965.0064.024
8.0 / 2.4	960.0080.024			965.0080.024

Disclaimer: All flow rates shown were obtained pumping water at 20 °C (68 °F) with zero suction and delivery heads. The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the users responsibility to ensure product suitability for use within their application. Watson-Marlow, LoadSure, Pumpsil, PureWeld XL, Bioprene, Marprene are registered trademarks of Watson-Marlow Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. GORE and STA-PURE are registered trademarks of W.L. Gore and Associates. Please state the product code when ordering pumps and tubing.

wmfts.com/global



07 August 2023